



LOADMAC 225 ULTRA

IT'S TIME FOR CHANGE



PROVEN IN AUSTRALIAN CONDITIONS



BUILT IN THE UK



CLASS LEADING 44HP KUBOTA ENGINE



WWW.LOADMAL.COM

LOADMAC 225 ULTRA



TECHNICAL SPECIFICATION

Load centre	600mm
Lifting capacity	2500kg
Unladen weight (Dependent on spec)	1990kg
Kubota 4 cylinder diesel engine	44hp – 33kw
Maximum engine RPM	2600
Drive wheels	3
Steering	Hydrostatic
Rear wheel steering	Slew ring
Rear wheel steering	180°
Wheel diameter	27" x 10.5"
Wheel base	1571mm
Truck length	2200mm
Truck width	2280mm
Truck height to cab roof	2206mm
Frame opening	1522mm
Maximum overhang on host vehicle	1150mm
Maximum gradability	56%
Maximum speed	12kph
Side shift	150mm
Tilting angles (Forwards/Backwards)	6.5/5.5° - 13° /12°
Reach	1032mm
Ground clearance (bottom of mast)	196mm
Maximum circuit service pressure	200 bar
Maximum driveline pressure	350-380 bar
Tilting carriage	Standard
Fixed mast	Standard
ROPS/FOPS cabin	Standard
Integrated Reach System	Standard
Man on the ground mounting controls	Standard



KEY OPTIONS

Multi-directional steering with mast safety monitor
Choice of tyre sizes and treads
Corporate paint colours
Specialist attachments
Integrated fork positioning
Telescopic forks

MAST HEIGHT OPTIONS

Available mast heights	3.1m / 3.6m
2.6m mast height minimum	2222mm
3.1m mast height minimum	2472mm
3.6m mast height minimum	2722mm
2.6m mast height maximum	4477mm
3.1m mast height maximum	4977mm
3.6m mast height maximum	5477mm

PHONE: 08 8262 1000

WEB: www.bpfequipment.com.au

EMAIL: daniel@bpfequipment.com.au

