

LOADMAC 825 SUPER REACH

IT'S TIME FOR CHANGE



**PROVEN IN AUSTRALIAN
CONDITIONS**



BUILT IN THE UK



WWW.LOADMAC.COM

LOADMAC 825 SUPER REACH



TECHNICAL SPECIFICATION

Load centre	600mm
Lifting capacity	2500kg
Unladen weight (Including iSR one-side offload system)	2725kg
Yanmar 4 cylinder diesel engine	49hp – 36.5kw
Maximum engine RPM	3000
Drive wheels	3
Steering	Hydrostatic
Rear wheel steering	Slew ring
Rear wheel steering	180°
Rear wheel diameter	27"
Wheel base	1625mm
Truck length (27" front wheel)	2140mm
Truck width	2350mm
Truck height to cab roof	2410mm
Frame opening	1640mm
Maximum overhang on host vehicle	1350mm
Maximum gradability	35%
Maximum speed	14.5kph
Side shift	150mm
Tilting angles (Forwards/Backwards)	12°/10°
Reach	2400mm
Ground clearance	300mm
Maximum circuit service pressure	250 bar
Maximum driveline pressure	350 bar
Tilting carriage	Standard
Fixed mast	Standard
ROPS/FOPS cabin	Standard
Integrated Second Reach (ISR)	Standard



KEY OPTIONS

- Multi-directional steering with mast safety monitor
- Choice of tyre sizes and treads
- Corporate paint colours
- Specialist attachments
- Additional Tilting CAM Mast for Additional Reach (Australian Spec)

MAST HEIGHT OPTIONS

Available mast heights	3.1m / 3.6m
3.1m mast height minimum	2430mm
3.6m mast height minimum	2690mm
3.1m mast height maximum	4800mm
3.6m mast height maximum	5380mm

PHONE: 08 8262 1000

WEB: www.bpfequipment.com.au

EMAIL: daniel@bpfequipment.com.au

